

# INDUSTRIAL DUPLO

Double step ladder with two climbs  
step 8 cm wide.

Step ladder for professional use made of ribbed aluminum, the rungs are welded to the amounts leading to a very solid and sturdy structure.

## TECHNICAL

- Distance between steps: 25 cm;
- Steps nonskid plans: 8 cm;
- Ability: 150 kg;
- Number of steps: 3 - 13;
- Heights in ladder: from 0,69 to 3,06 m;
- Tested 225 kg.

## EQUIPMENT

- Iron bar and anti opening hinge;
- Non-slip rubber plates with ergonomic design;
- Reinforcements anti-flexion in larger steps;
- Use and maintenance manual;
- Certificate of conformity with standard EN 131;
- Identification label.

The European Standard EN 131 prohibits be in both last steps in the absence of guard rails.  
The platform account as a step.

## OPTIONS

- Guard rails;
- Handrail (1 to 4 units per ladder);
- Wheel kit (2 or 4 units per ladder).

These accessories/options allow convenient and safe professional use:

- With the optional aluminum rails, it is possible to use the last step with a feeling of safety and comfort on the part of the worker.
- The wheels (2 or 4 by ladder) allow you to carry the ladder quickly recovering time and effort.
- Ramp handrail (from 1 to 4 per unit ladder) allows comfortable grip during ascent.

Optional accessories are provided with fixing screws which apply to holes made directly on the product.

\*See page 23



REF							KG	€
		m	m	m	m	mm		
10017	2x3	0.69	1.98	0.43	0.17	80x25	3.50	
10018	2x4	0.92	2.21	0.46	0.17	80x25	5.00	
10019	2x5	1.17	2.67	0.49	0.17	80x25	6.50	
10020	2x6	1.40	2.90	0.51	0.17	80x25	8.00	
10021	2x7	1.62	3.12	0.54	0.17	80x25	9.50	
10022	2x8	1.86	3.36	0.56	0.17	80x25	11.00	
10023	2x9	2.10	3.60	0.59	0.17	80x25	12.50	
10024	2x11	2.57	4.07	0.64	0.17	80x25	14.50	
10025	2x13	3.06	4.56	0.69	0.17	80x25	17.50	

