

INDUSTRIAL MAX PLUS

Wide step ladder with handrail professional use port tray.

Step ladder for professional use made of ribbed aluminum which provides maximum robustness. Steps welded to the amounts creating a very strong structure. It is 50 mm wider and have a working platform more spacious and comfortable which increases the comfort level of the worker's job. Ladder equipped with handrails to climb holder tray. Industrial Max Plus complies with European safety standard EN 131.

TECHNICAL

- Number of steps: 5 - 12;
- Distance between steps: 25 cm;
- Depth steps: 8 cm;
- Profile front amount: 80x25 mm;
- Profile rear pillar: 50x25 mm;
- Closed width: 26 cm;
- Width uphill: from 52 to 71 cm;
- Dimensions platform: 25,50x35 cm;
- Guard rails height: 60 cm;
- Platform height: from 1,16 to 2,77 m;
- Total height of the ladder: from 2,05 to 3,80 m;
- Capacity: 150 kg.

EQUIPMENT

- Reinforced anti-slip aluminum platform;
- Anti opening safety hook on the platform;
- Take anti opening/closing in galvanized steel;
- Handrails rise;
- Port-tray;
- Non-slip rubber tacos with ergonomic design;
- Tool holder tray;
- The reinforcement anti-flexion wider step;
- Rear enhanced with new joint;
- Use and maintenance manual;
- Certificate of conformity with standard EN 131;
- Identification label.



| REF | | | | | | | KG | € |
|---------|----|------|------|------|------|------|-------|---|
| | | m | m | m | m | m | | |
| 10737.1 | 5 | 2.05 | 1.16 | 3.16 | 0.52 | 0.26 | 10.00 | |
| 10738.1 | 6 | 2.30 | 1.39 | 3.39 | 0.54 | 0.26 | 11.00 | |
| 10739.1 | 7 | 2.55 | 1.61 | 3.61 | 0.57 | 0.26 | 13.00 | |
| 10740.1 | 8 | 2.80 | 1.85 | 3.85 | 0.60 | 0.26 | 15.00 | |
| 10741.1 | 10 | 3.30 | 2.30 | 4.30 | 0.65 | 0.26 | 17.00 | |
| 10742.1 | 12 | 3.80 | 2.77 | 4.77 | 0.71 | 0.26 | 20.00 | |

