

PALCO EXTRA

Fixed platform with two drive wheels and handles.

Built in extruded aluminum with a strong and durable quality, increase gradient is large and convenient, has a slope 48° with anti-skid steps 200 mm depth and a 200 mm distance between steps. To avoid excessive transportation costs ladder is commercialized disassembled, following a book assembly instructions. The back is perpendicular to the ground to allow the user access to a close wall or machines. Ideal for access to trucks, access equipment, access to industrial equipment.

TECHNICAL

- Step width: 240 mm;
- Standard deck length: 400 mm (possibility of extending 200-200 mm);
- Distance between step: 200 mm;
- Tilt rise: 48°;
- Step grooved aluminum-slip plane (series);
- With 2 handles and 2 wheel diameter: 125 mm at the rear;
- 4 non-slip feet;
- Extremely strong construction by the side of large profiles;
- Capacity: 200 kg.



PLATFORMS

AVAILABLE

- In 3 widths 600, 800 and 1000 mm;
- No handrails and railings;
- On request steps in grating galvanized steel.

OPTIONS

- Extra stage with handrails 40 mm;
- 3 types of handrails;
- Side railing law;
- Left side railing;
- Front handrail;
- All rails are fitted with 100x20 mm footers.



PALCO EXTRA				WIDTH 600 mm			
				REF		KG	€
	m	m	m				
2	0.39	2.40	0.85	30011	2	16.00	
3	0.59	2.60	1.05	30012	3	20.00	
4	0.79	2.80	1.25	30013	4	25.00	
5	0.99	3.00	1.45	30014	5	29.00	

WIDTH 800 mm				WIDTH 1000 mm			
REF		KG	€	REF		KG	€
30015	2	18.00		30019	2	20.00	
30016	3	22.00		30020	3	25.00	
30017	4	28.00		30021	4	33.00	
30018	5	33.00		30022	5	38.00	

